

HSF RoHS

SPECIFICATIONS

Housing: Thermoplastic,UL94V-0 (PBT)

Color: Black

Contact:Copper Alloy

Shell:Zinc Alloy

Voltage Current Rating:1.0Amp.250V AC

Insulation Resistance:500MΩ Min.

Contact Resistance:35mΩ Max.

Dielectric Withstanding Voltage:500V AC

Temperature Range:-40°C to +105°C

No. of Pin	DIMENSIONS				
	A	B	C	D	E
50	52.55	46.37	30.48	39.57	34.35
68	64.00	57.77	41.91	51.00	45.78
100					

▲M2-56/M2.6

Ordering Information

6311-F XXX S D XX MNA OX

No.of Pins
50P,68P,100P

Connector Type
S=Straight

Contact Plating
G0:Gold Flash
S0:Gold Flash/Tin
S1:3U" ⌀

OPERATION

DRAW

YiYuSheng

17.11.23

SCALE

FIT

X.X ±0.30

CHECK

UNIT

mm

X.XX ±0.20

X.XXX ±0.10

Angle ±3°

DIM TOL

APPROVE

SIZE

A4

SHEET

1/1

PROJ.

⌀

PART NO.

6311FXXXSDXXMNAOX

TITLE:

SCSI DB Female 180°

REV

DATE

MODIFICATION DESCRIPTION

CHANGE

1

2

3

4

5

6

7

8

9

G
F
E
D
C
B
A

G
F
E
D
C
B
A